




FAGOR INDUSTRIAL

B° Sancholopetegui, 22  
Apdo. 17  
20560 OÑATI (ESPAÑA)  
Tel: +34 943 71 80 30  
Fax: +34 943 71 81 81  
---  
[www.fagorindustrial.com](http://www.fagorindustrial.com)



## GAS FRYER, FG-710

### DESCRIPTION

Made of stainless steel  
Capacity: one 15 litre oil/well.  
Tank equipment: 1 basket 250x280 or 2 small baskets 250x135 mm .  
Cast iron burners.  
Thermostat temperature control 60 °C to 195 °C.  
Automatic burner ignition by means of an electromagnetic valve, with pilot light and thermocouple. Safety thermostat.  
Drainage tap.  
Power: 13000 Kcal/h. (15.11 kW).  
Dimensions: 350 x 750 x 850 mm.

### DATA

Electric power	kW	0,05	Water consumption	lit/h	
Electrical intake			Water pressure	Kg/cm <sup>2</sup>	
230V - 1 + N + T	2x1,5+T - 2 A		Steam power	kg/h	
230V - 3 + T			Steam pressure	Kg/cm <sup>2</sup>	
400V - 3 + N + T			Air consumption	NI/min	
Gas power	kcal/h	12994,6	Air pressure	Kg/cm <sup>2</sup>	
Gas power	kW	15,11	Length	mm	350
Natural Gas			Depth	mm	750
Consumption	m <sup>3</sup> /h	1,59	Height	mm	850
Natural Gas			Net weight	kg	57
pressure	g/cm <sup>2</sup>	18	Gross weight	kg	68
LPG Consumption	Kg/h	1,25	Volume	m <sup>3</sup>	0,3451
LPG pressure	g/cm <sup>2</sup>	37			




Distribuidor oficial:





B° Sancholopetegui, 22  
Apdo. 17  
20560 OÑATI (ESPAÑA)  
Tel: +34 943 71 80 30  
Fax: +34 943 71 81 81  
---  
[www.fagorindustrial.com](http://www.fagorindustrial.com)



## ELECTRIC FRYER, FE-710

### DESCRIPTION

Made of stainless steel  
Capacity: one 15 litre oil/well.  
Tank equipment: 1 basket 250x280 or 2 small baskets  
250x135 mm .  
Shielded heating elements in stainless steel.  
Pilot light for heating. Control by thermostat (60 °C to 195  
°C).  
Safety thermostat. Drainage tap.  
Power: 13.5 kW.  
Dimensions: 350 x 750 x 850 mm.

### DATA

Electric power	kW	13,5	Water consumption	lit/h	
Electrical intake			Water pressure	Kg/cm <sup>2</sup>	
230V - 1 + N + T	2x16+T - 80 A		Steam power	kg/h	
230V - 3 + T	3x16+T - 40 A		Steam pressure	Kg/cm <sup>2</sup>	
400V - 3 + N + T	4x2,66+T -		Air consumption	NI/min	
25 A			Air pressure	Kg/cm <sup>2</sup>	
Gas power	kcal/h		Length	mm	350
Gas power	kW		Depth	mm	750
Natural Gas Consumption	m <sup>3</sup> /h		Height	mm	850
Natural Gas pressure	g/cm <sup>2</sup>		Net weight	kg	57
LPG Consumption	Kg/h		Gross weight	kg	68
LPG pressure	g/cm <sup>2</sup>		Volume	m <sup>3</sup>	0,3451




Distribuidor oficial:





FAGOR INDUSTRIAL

B° Sancholopetegui, 22  
Apdo. 17  
20560 OÑATI (ESPAÑA)  
Tel: +34 943 71 80 30  
Fax: +34 943 71 81 81  
---  
[www.fagorindustrial.com](http://www.fagorindustrial.com)



## GAS FRYER, FG-720

### DESCRIPTION

Made of stainless steel  
Capacity: two 15 litre oil/well.  
Tank equipment: 1 basket 250x280 or 2 small baskets 250x135 mm .  
Cast iron burners.  
Thermostats temperature control 60 °C to 195 °C.  
Automatic burner ignition by means of an electromagnetic valve, with pilot light and thermocouple. Safety thermostat.  
Drainage taps.  
Power: 26000 Kcal/h. (30.22 kW).  
Dimensions: 700 x 750 x 850 mm.

### DATA

Electric power	kW	0,05	Water consumption	lit/h	
Electrical intake			Water pressure	Kg/cm <sup>2</sup>	
230V - 1 + N + T	2x1,5+T - 2 A		Steam power	kg/h	
230V - 3 + T			Steam pressure	Kg/cm <sup>2</sup>	
400V - 3 + N + T			Air consumption	NI/min	
Gas power	kcal/h	25989,2	Air pressure	Kg/cm <sup>2</sup>	
Gas power	kW	30,22	Length	mm	700
Natural Gas			Depth	mm	750
Consumption	m <sup>3</sup> /h	3,18	Height	mm	850
Natural Gas			Net weight	kg	104
pressure	g/cm <sup>2</sup>	18	Gross weight	kg	119
LPG Consumption	Kg/h	2,5	Volume	m <sup>3</sup>	0,6567
LPG pressure	g/cm <sup>2</sup>	37			




Distribuidor oficial:





FAGOR INDUSTRIAL

B° Sancholopetegui, 22  
Apdo. 17  
20560 OÑATI (ESPAÑA)  
Tel: +34 943 71 80 30  
Fax: +34 943 71 81 81  
---  
www.fagorindustrial.com



## ELECTRIC FRYER, FE-720

### DESCRIPTION

Made of stainless steel  
Capacity: two 15 litre oil/well.  
Tank equipment: 1 basket 250x280 or 2 small baskets  
250x135 mm .  
Shielded heating elements in stainless steel.  
Pilot light for heating. Control by thermostats  
(60 °C to 195 °C).  
Safety thermostats. Drainage taps.  
Power: 27 kW.  
Dimensions: 700 x 750 x 850 mm.

### DATA

Electric power	kW	27	Water consumption	lit/h	
Electrical intake			Water pressure	Kg/cm <sup>2</sup>	
230V - 1 + N + T	2x16+T - 80		Steam power	kg/h	
A			Steam pressure	Kg/cm <sup>2</sup>	
230V - 3 + T	3x16+T - 40 A		Air consumption	NI/min	
400V - 3 + N + T	4x2,66+T -		Air pressure	Kg/cm <sup>2</sup>	
25 A			Length	mm	700
Gas power	kcal/h		Depth	mm	750
Gas power	kW		Height	mm	850
Natural Gas Consumption	m <sup>3</sup> /h		Net weight	kg	104
Natural Gas pressure	g/cm <sup>2</sup>		Gross weight	kg	119
LPG Consumption	Kg/h		Volume	m <sup>3</sup>	0,6567
LPG pressure	g/cm <sup>2</sup>				



Distribuidor oficial:

